

Stock List Product

No.	Name of Product	Brand	Specification	Stock	Satuan
REGULATOR					
1	Gas Pressure Regulator	Tormene	Gas Pressure Regulator TA950 Hp + SSV DN 1" x 1" Npt - 20/+60C Impulse Internal set point range 0.35-0.45 bar N4 extra spring for Reg. set point range extantion SN; 210126, 210127, 210128, 210129	3	ea
2	Gas Pressure Regulator	Tormene	Gas Pressure Regulator TA950+SSV DN 2" x 2" Npt, TA950 Hp+SSV #150 RF DN 50, TA950 Hp+SSV Flanged Ansi 150 RF -20/+60C Impulse External	1	ea
3	Pressure Regulator SHTF Valve	Tormene	Pressure Regulator SHTF Valve TA 956FC+SSV DN 1"x1" #150, TA956C+SSV std Temp -20/+60°C, Pilot Active. TA981FC SSV Head CX640 Flange	4	ea
4	Pressure Regulator SHTF Valve	Tormene	TzA956FC+SSV #150 DN 2"x2" TA956FC+SSV ANSI 150 RFM (P1=0.6-20;P2>0.3) DN 2"x2" -20/+60°C Int. Silencer 100 Pilot Active. TA981FC SSV Head CX640 Flow Left to Right ® (SN: R60624A0432, R60624A0433)	3	ea
5	Pressure Regulator SHTF Valve	Tormene	TA956FC+SSV #150 DN 2"x2" TA956FC+SSV ANSI 150 RFM (P1=0.6-20;P2>0.3) DN 2"x2"-20/+60°C Int. Silencer 100 Pilot Active TA981FC SSV Head CX640 Flow Right To Left (L) (SN: R60624A0430, R60624A0431)	3	ea

6	Pressure Regulator SHTF Valve	Tormene	Pressure Regulator SHTF Valve TA 956FC+SSV 3" #150 R to L, TA956 FC+SSV Ansi 150 RF DN 3"x3" -20/60 C, Pilot Active TA981FC SSV Head CX640 Flow Right To Left	3	ea
7	Pressure Regulator SHTF Valve	Tormene	Pressure Regulator SHTF Valve TA 956FC+SSV 3" #150 L to R, TA956 FC+SSV Ansi 150 RF DN 3"x3" -20/60 C, Pilot Active TA981FC SSV Head CX640 Flow Left To Right	5	ea
8	Pressure Regulator SHTF Valve	Tormene	Pressure Regulator SHTF Valve TA 956FC+SSV 3" #300 L to R, TA956+SSV ANSI 300 RF DN 3"x3" -20/60 C, Pilot Active TA981FC SSV Head CX630 Flow Left to Right, Include Spring	1	ea
9	Pressure Regulator SHTF Valve	Tormene	<i>Pressure Regulator SHTF Valve TA 956FC+SSV 3" #300 L to R, TA956+SSV ANSI 300 RF DN 3"x3" -20/60 C, Pilot Active TA981FC SSV Head CX630 Flow Right to Left Include Spring</i>	1	ea
10	Pressure Regulator	Tormene	<i>Pressure Regulator TA 956 1" ansi 150 & SSV type Cx460 SN; R60221a0030</i>	1	ea
11	Regulator	Ergas	<i>Regulator Ergas</i>	4.200	ea
12	Regulator	Honeywell	<i>Regulator Hon 273 Range 1-4 Bar 2" #150 Thread SN: 2020/02/22236-3 (1), 2020/02/22236-3 (2), 2020/02/22236-3 (3), 2020/02/22236-3 (4), 2020/02/22236-3 (5), 2020/03/22236-4 (1), 2020/03/22236-4 (2), 2020/03/22236-4 (3), 2020/03/22236-4 (4)</i>	7	ea
13	Regulator	Honeywell	<i>Gas Pressure Regulator 372 Range 0-1 Bar 2" #150 DN: 50, PS; 20 bar SN: 1806189996</i>	1	ea

TURBIN, USM AND EVC					
14	EVC Hight Pressure	ELCORplus	Pressure: 0.8.....35 bar, Temperatur: -25....+70°C, SN: 2446105018 s/d 29	1	ea
15	EVC Primus 400	RMG	SN; 7 RMG 2446102188, 7 RMG 2446102190, 7 RMG 2446102191, 7 RMG 2446102192, (7 RMG 2446102193 (Cable length 10m)) Pres : 0.8 ...20 bar, Temp. -25...+70°C, 7 RMG 2446104439 s/d 43	4	ea
16	Turbin Meter	RMG	Turbin Meter Trz 03 G 250, 3" Ansi 150, Q Max = 400 m3/h, S/N = 815188 & 815189, PS 20 bar	1	ea
17	Turbin Meter	RMG	Turbin Meter Trz 03 G 250, 3" Ansi 150, Qmax: 400, Qmin: 20, PS: 20 bar, TS: -20/+80 C, SN: 841074, 841075	2	ea
18	Turbin Meter	RMG	Turbin Meter Trz 03 G 250, 4" Ansi 150, Q Max = 400 m3/h, Q Min = 20 S/N = 837094, 837095 PS 20 bar	2	ea
19	Turbin Meter	RMG	Turbin Meter Trz 03 G 400, 4" Ansi 150 DN 100 Qmax: 650, Qmin: 32 PS: 20 bar, TS: -20/+80 C, SN: 83	5	ea
20	Turbin Meter	RMG	Turbin Meter Trz 03 G 400, 6" Ansi 150, Q Max = 650, Q Min=32, PS=20 bar SN; 718351, 718352, 718353, 718354, 718355	5	ea
21	Turbin Meter	RMG	Turbin Meter Trz 03 G 65, DN 50 (2") Ansi 150, Q Max = 100 m3/h, S/N = 834074, 837089, 837090, 837091 PS 20 bar, Graphit Cast Iron	1	ea
22	Turbin Meter	RMG	Turbin Meter Trz 03 G 65, DN 50 (2") Ansi 150, Q Max = 100 m3/h, S/N = 843682 s/d 843691 PS 20 bar, Graphit Cast Iron	10	ea

23	Turbin Meter	RMG	Turbin Meter Trz 03 G. 100, 3" Ansi 150, Q Max=160, Q Min=16, PS=20 bar, SN; 718873,718880, 718883, 718884, 718885	4	ea
24	Turbin Meter	RMG	Turbin Meter Trz 03 G. 160, 3" Ansi 150, Q Max=250, Q Min=13, PS=20 bar, SN; 718500, 718501, 718503, 718505, 718506, 718507, 718508, 718509, 718886, 718887, 718888, 718889, 718891, 718892, 718895, 718897, 718898, 718910.	17	ea
25	Turbin Meter	RMG	Turbin Meter Trz 03 G. 160, 3" Ansi 150, Q Max=250, Q Min=13, PS=20 bar, SN; 718905, 718906.	1	ea
26	Turbin Meter	RMG	Turbin Meter Trz 03 G4000, 12" Ansi 150, DN 300, G 400 - 45, Qt: 1300, Qmax: 6500 m ³ /h, Qmin: 320 m ³ /h, TS: - 40/+40 C, Serial No: 843186	1	ea
27	USM	RMG	USM400DN0400 USM-GT-400, DN 400 (16") SN : 832859, 832860 Configuration Design: Standard Pressure Class: ANSI 150 RF Schedule: Schedule 40 Housing: ATEX w/ Junction Box Additional Options: None Language: English Measuring Units: Imperial (cbft, °F) Low Pressure Calibration: None High Pressure Calibration: Worktest w/ Nat. Gas Factory's Certificate: 3.1 Cert. (DIN EN 10204) Pressure Connection: Pr.conn. Swlk SS 6mm Options: None Standard Communications Prot. : Modbus Device-F Optional Analog Output: 4-20mA Output with HART & 2 x RS485	2	ea

			<i>Flow Operation Mode: Unidirectional Operation</i> <i>Extended Flow Range Qmin/2: Standard</i> <i>Region Of Operation: Other</i> <i>Special Marking/Packing: none / RMG Standard Power Supply 24 VDC</i> <i>Measurement Range Qmin 4240 cbft/h</i> <i>Measurement Range Qmax 529700 cbft/h Calibrated</i> <i>Measurement Range 1:125 Operating Side (in main direction of flow) righ</i>		
SPAREPARTS					
28	Baterai Lithium		<i>Baterai Lithium LP-3600 3.6V/16.5AH-17AH</i>	2	ea
29	Baterai Lithium		Baterai Lithium LP-3600 3.6V B-03D For EVC Primus 400	4	ea
30	Counter Meter		Counter Meter, Counter Assy'	600	ea
31	Coupling Meter	Ergas	<i>Coupling Meter Gas merk ERGAS</i>	18	ea
32	Coupling Meter Gas	Zenner	Coupling Meter Gas Npt 3/4", Size: M30*2 to NPT 3/4"	350	ea
33	Double Nipple		<i>Double Nipple 3/4</i>	1.003	ea

34	Flange Insulation Kit		Flange Insulation Kit 12" x #150, Style: 280, Type: F (RF), Model: L- Seal, Retainer: G10, Seal: Viton, Sleeve: Mylar, Washer: G10+ZPS, Size: 12" x #150	2	ea
35	Flange Insulation Kit	Flexiteck Uk	Flange Insulation Kit 2"x600#, Style 280 Type E (FF) Model E, Retainer Neoprene Face Phenolic Sleeve Washer Phenolic+ZPS	4	ea
36	Flange Insulation Kit	Flexiteck Uk	Flange Insulation Kit 16"x600#, Style 280 Type E (FF) Model E, Retainer Neoprene Face Phenolic Sleeve Washer Phenolic+ZPS	4	ea
37	Gear set turbine RMG	RMG	<i>Gear set turbine RMG</i>	1	set
38	Infra Red Cable		<i>Optical Redout Cable With USB Interface</i>	1	ea
39	Internal Module For Permanent Power Supply		<i>38.01.100.03 Internal Module For Permanent Power Supply</i>	3	ea
40	Piston Pump Lubrican Oil 1L		<i>90.59.266.00 Piston Pump+Adjusting Screw+Oil Tank SP 2131 Include 38.11.148.01 Stands For Oil 1L</i>	1	ea
41	Piston Pump+Adjusting Screw+Oil Tank		<i>90.59.266.00 Piston Pump+Adjusting Screw+Oil Tank SP 2132</i>	1	ea
42	Regulator konkit	Top Gas	<i>Regulator konkit merk top gas</i>	6.245	ea
43	Regulator konkit	Top Gas	<i>With Manometer</i>	2.561	ea

44	Sealtape	Onda	<i>Sealtape merk onda</i>	576	roll
45	Silincer SL-30	Tormene	Silincer SL-30 for Regulator TA956 DFO	1	ea
46	Spring D6		<i>Spring D6</i>	12	ea
47	Spring N		<i>Spring N 1512 OD</i>	41	ea
48	Spare Part Kit	Tormene	Spare Part Kit TA956 FC+SSV #150 DN 3"x3" LV 2	1	ea
49	Spare Part Kit	Tormene	<i>SPK TA956FC+SSV (L2) #300 DN 8" Sparepart Kit TA956+SSV (Level 2 Complete) Ansi 300 DN 8"x8", -20/+80 C</i>	2	ea
50	Spare Parts Kit	Tormene	Spare Parts Kit TA956DFO+SSV (L1) #150 DN 6", (Level 1 Soft Parts) Ansi 150 - (PN16) DN 6"x6" -20/+60C	1	ea
51	Spare Parts Kit	Tormene	<i>SPK PILOT TA981FC, Spare Parts Kit TA981FC, SPK</i>	2	ea
52	Spare Parts Kit for Pilots	Tormene	Spare Parts Kit for Pilots TA983FO, TA893FO+VRC05 STD TEMPERATURE, SSV Head, CX630 Spare Parts Kid std Temp	1	ea
53	Spare Part Kit	Honeywell	<i>SPK958SSVCX630-00, SSV Head CX630 Spareparts Kit</i>	2	ea

54	Stang Pressure Regulator		<i>Stang Pressure Regulator DN 100</i>	4	ea
55	Stang Valve		<i>DN 50</i>	25	ea
56	Valve Carier		<i>Valve Carier, Clip Assy 6" 150-1500#</i>	1	ea
57	Valve Sear Grease Yellow		<i>Valve Sear Grease Yellow (C60DC54-340B, 20 to 400 F)</i>	2	ea
58	VM24-1 Series		<i>VM24-1 Series, Connection 1/2" NPTF x 1/2" NPTM With Drain Plug</i>	6	ea
59	VM52 Series		<i>VM52 Series, Connection 1/2" NPTF x 1/2" NPTF</i>	4	ea
INSULATING JOINT					
60	Insolating Join 2" Ansi 600 API 5LB	ZHCX	<i>Insolating Joint 2" Ansi 600 lenght 350 mm no. produk: 202006003</i>	1	ea
61	Insolating Join	Meccanica	<i>Insolating Join 4" Ansi 300 API 5LB/X42 SN: 0241</i>	1	ea
62	Insolating Join	Meccanica	<i>Insolating Join 4" Ansi 300 API 5LB/X42-PSL2 SN: 0254, 0255, 0256, 0257,0258, 0259, 0261</i>	7	ea

63	Insulating Join	Meccanica	<i>Insulating Join NPS 2" Ansi 600 API 5L B W.T 3.91 mm GrB Length 350mm Design Pressure: 100 bar SN: 8662</i>	1	ea
64	Insulating Join	Meccanica	<i>Insulating Join NPS 2" Ansi 300 API 5L B W.T 3.91 mm GrB Design Pressure: 50 bar(G) SN: 0365,0366</i>	8	ea
65	Insulating Join	Meccanica	<i>Insulating Join NPS 3" Ansi 300 API 5L B W.T 3.91 mm GrB Length 500mm design Pressure: 50 bar SN: 0094,0095</i>	2	ea
66	Insulating Join	Meccanica	<i>Insulating Join NPS 3" Ansi 300 API 5L B W.T 3.91 mm GrB Length 500mm design Pressure: 50 bar SN: 0096,0097</i>	2	ea
67	Insulating Joint	Meccanica	<i>Insulating Joint NPS 8" Ansi 300 API 5LB W.T 8.18 Length 600 mm, SN: 2051, 2052</i>	2	ea
68	Insulating Joint	Nouvagingas	<i>Insulating Joint 1" 100 bar API 5L GR.B</i>	5	ea
69	Insulating Joint	Nouvagingas	<i>Insulating Joint 1-1/2" 100 bar</i>	5	ea
70	Insulating Joint	Nouvagingas ZHCX	<i>Insulating Joint 4" 64 bar Sch. 80</i>	1	ea
71	Insulating Joint	Meccanica	<i>Insulating Joint 4" Ansi 600 API LB SN: 0114</i>	1	ea
72	Insulating Joint	Meccanica	<i>Insulating Joint 4" Ansi 600 API LB/X42 SN: 0114, 0115, 0117, 0118</i>	3	ea

73	Insulating Joint	Meccanica	<i>Insulating Joint 4" Ansi 600 API LB/X42 SN: 0116, 0117</i>	2	ea
74	Insulating Join	Meccanica	<i>Insulating Join NPS 2" Ansi 150 API 5L B W.T 3.91 mm GrB Length 300mm Design Pressure : 25 bar, SN:1427 S/d 1436</i>	8	ea
75	Insulating Joint	Meccanica	<i>Insulating Join NPS 3" Ansi 150 API 5L B W.T 3.91 mm GrB Length 400mm Design Pressure: 25 bar SN: 2953,2954,2955</i>	4	ea
76	Insulating Joint	Meccanica	<i>Insulating Joint NPS 4" Ansi 150 API 5LB W.T 6,02mm GrB Ansi 150 Length 400mm Design Temperature: -10°C.+ 70°C. Design Pressure: 25 Barg SN:(1915, 1916), 2034,2035,2036,2037,2038,2039</i>	8	ea
77	Insulating Joint	Meccanica	<i>Insulating Joint NPS 6" Ansi 150 API 5LB W.T 7.11 mm GrB Ansi 150 Length 500mm Design Temperature: -10°C.+ 70°C. Design Pressure: 25 Bar(g) SN:1977,1978,1979,1980</i>	6	ea
78	Insulating Joint	Meccanica	<i>Insulating Joint NPS 8" Ansi 150 API 5LB W.T 8.18 Length 500 mm, SN: 1294, 1295</i>	2	ea
ORIFICE					
79	Orifice Fitting Dual Chamber	Canalta	<i>Orifice Fitting Dual Chamber 10" #600 WF</i>	1	ea
80	Orifice Fitting Dual Chamber	Canalta	<i>Orifice Fitting Dual Chamber 3" #150 WF</i>	2	ea
81	Orifice Fitting Dual Chamber	Canalta	<i>Orifice Fitting Dual Chamber 3" #300 WF</i>	1	ea

82	Orifice Fitting Dual Chamber	Canalta	<i>Orifice Fitting Dual Chamber 3" #600 FF</i>	2	ea
83	Orifice Fitting Dual Chamber	Canalta	<i>Orifice Fitting Dual Chamber 4" #300 FF</i>	1	ea
84	Orifice Fitting Dual Chamber	Canalta	Orifice Fitting Dual Chamber 4" #150 WF, Dual Chamber Fitting SCH 40 FSS Internals, Soft Seal, 150 WxF	2	ea
85	Orifice Fitting Dual Chamber	Canalta	<i>Orifice Fitting Dual Chamber 4" #300 WF</i>	4	ea
86	Orifice Fitting Dual Chamber	Canalta	<i>Orifice Fitting Dual Chamber 4" #600 WF</i>	1	ea
87	Orifice Fitting Dual Chamber	Canalta	<i>Orifice Fitting Dual Chamber 6" #300 WF Sch 40, SN: D0603214M5, D0604060M5</i>	2	ea
88	Orifice Fitting Dual Chamber	Canalta	<i>Orifice Fitting Dual Chamber 8" #300 WF</i>	1	ea
89	Orifice Plate	Canalta	<i>Orifice Plate 6" x1/8</i>	2	ea
VALVE					
90	Ball Valve		Ball Valve PE 63 Full Bore, Coupling Collar and Base Plate	8	ea

91	Ball Valve		Valve 1/2" 150LB Body: A216 WCB, SS136, PTFE, SN: T0388,T0386	2	ea
92	Ball Valve	Cameron	Ball Valve A105 2" #300, Body A216 Model 310L Ball SS316 WCB SN: 121771-001,121771-002, 121771-003, 121771-004, 121771-005, 121771-006, 121771-007	7	ea
93	Ball Valve	Cameron	Ball Valve A105 4" #300 (GROOVE) Cameron 3 piece,SN: 180933026-08	2	ea
94	Ball Valve	Cameron	Ball Valve A105 4" #300, Merk Cameron 2 piece	1	ea
95	Ball Valve	Cameron	Ball Valve A105 8" #300	1	ea
96	Ball Valve Armatury		Ball Valve size 10" #300 Armatury	1	ea
97	Ball Valve	TEK	Ball Valve 1/2" 1500	1	ea
98	Ball Valve Floating	FLV	Ball Valve Floating 1/2" #800 SWXNPT (100 mm Nipple) Body : A105N Stem : F316, Ball : F316,RPTEF, Lever SN: 2418011 s/d 2418021	11	ea
99	Ball Valve Floating	FLV	Ball Valve Floating 3/4" #800 SWXNPT (100 mm Nipple) Body : A105N Stem : F316, Ball : F316,RPTEF, Lever Temp. -29-150°C merk FLV SN : 2418022 s/d 27	6	ea
100	Ball Valve floating	TEK	Ball Valve floating 1" #800	2	ea

101	Ball Valve	Cameron	Ball Valve NPT 1/2" Class 1500, SN : 17260 s/d 17271	12	ea
102	Ball Valve NPT 3/4" Class 1500	Cameron	Ball Valve NPT 3/4 Class 1500 Sn: 16756, 19891 s/d 19899	10	ea
103	Ball Valve Silver Floating	Turbo	Ball Valve Floating two piece 2" 150 Seat: RPTFE, WCB, Ball: 304, Max. Temp : -29~120°C	2	ea
104	Ball Valve Trunnion		Ball Valve trunnion 2" 150LB full welded, Body 105 Stem A182 F6A Seat A105 + ENP SN; T 5130, 5139, 5152, 5122	4	ea
105	Ball Valve Trunnion		Ball Valve trunnion 2" 150LB three piece, Body 105 Stem A182 F6A Seat A105 + ENP SN; T 0439, 0440, 0460, 0510, 0547, 0564, 0588	6	ea
106	Ball Valve Trunnion	FLV	Ball Valve Trunnion Mounted 4" #150LB Body : A105N Stem : F316, Ball : F316, RPTEF, Lever SN : 2417001 s/d 2417008	8	ea
107	Check Valve	YONEKI Japan	Check Valve ASTM A105 OR A216 GR WCB #300 RF 4" Max temp : 400° C SN: 190772	2	ea
108	Check Valve Swing	FLV	Check Valve 4" #150 RF Body : WCB Trim : 1# Temp : -29-425°C SN: 2417009, 2417010	2	ea
109	Check Valve Waver	Vastas	Chek Valve Waver size 2", type E43D, Dual Disc Wafer PN 10-100 DN 50 NPS 2	1	ea
110	Plug Valve		Plug Valve 2" #150, Body: A216 WCB, Seat: PTFE, SS304, SN:T021, T024	2	ea

111	Pressure Control Valve	Azbil	<i>Pressure Control Valve 1" #150</i>	2	ea
112	Pressure Control Valve	Azbil	<i>Pressure Control Valve 2" #300 Body A216 WBC Range 0.8-2.4 bar SN: E015289</i>	12	ea
113	Pressure Control Valve	Azbil	<i>Pressure Control Valve 3" #300</i>	3	ea
114	Pressure Control Valve 4" #300	Azbil	<i>Pressure Control Valve 4" #300</i>	1	ea
115	Pressure Control Valve 6" #300	Azbil	<i>Pressure Control Valve 6" #300</i>	2	ea
116	PSV	Farris	<i>PSV 2" Set Pressure , Type 26HA12-120 SN: 979552-1-A10, 979553-1-A10, Set Press : 690 psig</i>	2	ea
117	Butterflay Valve WCB	TEK	<i>Butterflay Valve WCB 4" #150</i>	6	ea

118	Safety Relief Valve	Honeywell	Safety Relief Valve HON 832 Duty Tariff Code: 84814090 SN: (2307145613), 2407167332 s/d 2407167341Country of origin: GermanyConfigured Model Nbr: HON832-A-A- ABEA-MM-C-C-O-AABAA000-A0A0000-BMedium: A- Natural Gas (acc. G260) Temperature Range/Class: -20 to +60 deg C/Cl.2; EN334Body Material: A-Al-alloy Inlet Size: B-12 mmOutlet Size: E-20 mmExternal Fittings: A-ISO 8434-1 (standard) Max Allowable Pressure PS: M-100 barMax Inlet Pressure Pu max: M-100 barOrifice Size: C- 8mm KG-value [m³/(h*bar)]: A-32Spring range wds: C-2-8 barConnection; Vent Line: 0-without (internal) Diaphragm Material: A-NBR (Standard)Sealing Material: A-NBR (Standard)Paint Specification: B-Un-PaintedPaint Colour (Final Gloss): A-Anodized (black) Name Plate: A- German/English/FrenchTagging (optional): 0- NoneOutdoor Type: 0-NoSpecific requirements: 0-NoTest Certificate - EN10204: A-EN 10204-3.1 3rd Party nominated: 0-NoneMaterial Certificate - EN10204 A-EN 10204 -3.1Material Test Party: 0-NoneTest by 3rd party: 0-NoneSpecial Test: 0-NonePaint Report: 0-No PED (2014/68/EC): A-SEP acc. PED art. 4; section 3Certificate Language: B-EnglishTop-Level Product: A-Yes	11	ea
PRESSURE GAUGE, TEMPERATURE GAUGE, AND TRANSMITTER					

119	Pressure Transmitter	Rosemount	cal. 0-500 psi SN : 21SIPG3721618	1	ea
120	Pressure Gauge	Ashcroft	Pressure Gauge 0...1500 PSI, Model: 45-1209-SL-04L, Dual size: 4.5 Inch, Type: 1209	2	ea
121	Pressure Gauge	Ergas	PG 10 bar 150 Psi	2	ea
122	Pressure Gauge	WIKA	PG 10 bar 150 Psi	2	ea
123	Pressure Gauge	Ergas	PG 100 bar 1500 Psi	1	ea
124	Pressure Gauge	Ergas	PG 9 bar 90 Psi	1	ea
125	Pressure Gauge		Type FX550 Dial 4-1/2" 0...1000 mbar, 2" Pipe Mount, Vertical Pipe Mounting Conn 1/2" NPT-M	4	ea
126	Pressure Gauge		Model PX45 BT-D30 N2 G NS 115mm 0 + 10 Bar, Bottom Mounting, 1/2 NPT M Conection Glycerin, Range: 0...25 Bar & 0...350 psi	1	ea
127	Pressure Gauge		Type PX45 dial 4.5"/115mm Bottom Mounting, 1/2 NPT M Conection Glycerin, Range: 0...10 Bar & 0...600psi	4	ea
128	Pressure Transmitter	Rosemount	2051 CF Series, cal 1000 in H2O SN: 02766322	1	ea

129	Pressure Transmitter	Rosemount	Cal 0 - 1200 Psi G, Inline, Model: 3051TG4A2B21AB4E5M5DOQ8S5Y2, SN: 24SIPG3828028, 24SIPG3828029, c/w Rosemount Manifold 0306, Model: 0306RT22BA11	2	ea
130	Temperature Gauge	WIKA	TG54.100DS-4-FBDZ-ND-B0345GZ-ZZZZ1ZZ, Model: TG54.100, Accuracy Class: Class 1 Per EN 13190, Nominal Size: 100, Connaction Location: Back Mount, Adjustable, Connection Design: 4, Compression Fitting, Sliding on stem, Process Connection: 1/2 NPT, Scale Range: 0...200°F, Stem Diameter: 6 mm, Insetion Length L1: 345, SN:	2	ea
131	Temperature Transmitter	Rosemount	Hart, Cal 0 - 150 Degf, Model: 3144PD1A1E5M5Q4XA, SN: 24SITC3642896, 24SITC3642897, C/w Rosemount Temperature Transmitter Sensor & Thermowell, Model: 214CRTSMB1S4M0340SLE5XAXW, 114CM0270PAN2SC070AQ8R21XW	2	ea
132	Thermometer Gauge 53 inc. thermowel Threaded TW15		TG53.5ZD5-4-FBDC-ND-WOSOHZZ-ZZZZ, Thermometer Gauge inc. thermowel, Bimetal thermometer, process grade according to ASME B40.200 Accuracy class: +/- 1% of full Scale Nominal size: 5", Connection design: 4, compression fitting, sliding on stem Process connection: 1/2 NPT Scale range: 0°F....200°F, 2nd scale: 2nd scale -C Stem diameter: 1/4" Insertion length ll: 5". TW1S-H-A-M-NE-U D-00064-0004S-G3-A-0220-0160-ZZ-ZZ00102 Threaded Thermowell TW1S, solid machined Specification according to data sheet: TW9S.1S Process thread [P or E]: 3/4 NPT Connection to thermometer [N]: 1/2 NPTF Insertion length [U]: 64 mm Head length [H]: 45 mm Bore size [B or d1]: 0.260 inch (6.6 mm) Root diameter [Q]: 22 mm Tip diameter [V or F3]: 16 mm Bore depthl stem length (US) [A]: 102 mm Tip thickness [Tt]: 0.250 inch (6.4 mm)	2	ea

133	Thermometer Gauge TG50		Thermometer Gauge TG50 (125mm/5") 0..140°F & 0..60°C, 1/2" Npt Connection, Dry, Bulb: Suit to Thermowell (L) x 6.3mm (D), Serial Number: TM601-AE1017 S/d TM601-AE1018	2	ea
134	Thermometer Gauge TG50		<i>Thermometer Gauge TG50 dial (125mm/5") SL 6"/125mm, Mounting Connector NPT 1/2", Dry Range: 0...60C & -35...140F</i>	2	ea
FITTING STEEL					
135	Transition Fitting	KS	Transition Fitting 3/4" x 20mm	138	ea
136	Elbow	Borfit	<i>Elbow 125-45</i>	2	ea
137	Elbow	Borfit	<i>Elbow 180-90</i>	3	ea
138	Elbow	ELBOR	<i>Elbow 180-90</i>	11	ea
139	Elbow	Borfit	<i>Elbow 20-90</i>	6	ea
140	Elbow	Borfit	<i>Elbow 32-90</i>	1	ea
141	Elbow	Borfit	<i>Elbow 63-45</i>	2	ea

142	Elbow	Borfit	<i>Elbow 90-45</i>	62	ea
143	Elbow	+GF+	Elbow 90x90mm	1	ea
144	Elbow	Borfit	<i>Elbow Kit 180-45</i>	10	ea
145	Elbow	Borfit	<i>Elbow Kit 20-45</i>	3	ea
146	Elbow Kit	Borfit	<i>Elbow Kit 32-45</i>	9	ea
147	Elbow	Kimplas	Elbow 45 x 63mm	1	ea
148	Equal Tee	Fussion	Equal Tee 20mm	80	ea
149	Equal Tee	Borfit	<i>Equal Tee 180</i>	3	ea
150	Equal Tee	Borfit	<i>Equal Tee 32</i>	7	ea
151	Equal Tee	Borfit	<i>Equal Tee 63</i>	1	ea

152	Equal Tee	Borfit	<i>Equal Tee 90</i>	3	ea
153	Equal Tee	ELBOR	<i>Equal Tee 90 mm</i>	10	ea
154	Equal Tee	Borfit	<i>Equal Tee Kit 20</i>	11	ea
FITTING PE					
155	Pipa HDPE Ø 180 x 6m		<i>Pipa PE 180 x 6m</i>	73	btg
156	Pipa HDPE Ø125mm		<i>Pipa HDPE Ø125mm</i>	63	btg
156	Pipa HDPE Ø180mm x 12m		<i>Pipa HDPE Ø180mm</i>	1	btg
157	Tapping Saddle	ELBOR	<i>Tapping Saddle 6x20</i>	9	ea
158	Tapping Tee	Borfit	<i>Tapping Tee 63-20</i>	2	ea
159	Tapping Tee	Borfit	<i>Tapping Tee 63-32</i>	1	ea

OTHERS					
160	Analog Output		Analog Output 4-20mA Accessory Primus/Prilog	1	ea
161	Assembly SDV		Assembly SDV, Included Actuator Bettis for Ball Valve 4" 300 model: CBB725 SR 80	1	unit
162	Bimetal Thermometer		Bimetal Thermometer 5"/4	4	ea
163	Box Panel		Box Panel	2	ea
164	Catridge Filter		Catridge Filter 6"	3	ea
165	Coupler	Borfit	Coupler 125	1	ea
166	Coupler	Borfit	Coupler 180	15	ea
167	Coupler	Borfit	Coupler 20	199	ea
168	Coupler	ELBOR	Coupler 20	10	ea

169	Coupler	Borfit	Coupler 32	5	ea
170	Coupler	Fussion	Coupler 32mm	47	ea
171	Coupler	Borfit	Coupler 63	7	ea
172	Coupler	ELBOR	Coupler 63	10	ea
173	Coupler	Fussion	Coupler 90mm	6	ea
174	Coupling Meter Gas	BG4BJT	Coupling Meter Gas	194	ea
175	Coupling Meter Gas	KS	uk. 3/4 M 30x2	304	ea
176	Differential Pressure Indicator DP/F10	Guglielmi Dalino	<i>Differential Pressure Indicator DP/F10, 0-1000 mBar Connections 1/4" Gas PN100 (Dual Scale) With Psid</i>	22	ea
177	Differential Pressure Indicator DP/G	Guglielmi Dalino	<i>Differential Pressure Indicator DP/G, 0-600 mBar Connections 1/4" Gas PN100 (Dual Scale) With Psid</i>	5	ea
178	Differential Pressure Transmitter	Rosemount	<i>cal 200 in H2O Model: 0305RC52B11BEL4 SN: 21SIPG3721622, 21SIPG3721623,</i>	1	ea

179	End Cap	Borfit	End Cap 180mm	6	ea
180	End Cap	Fussion	End Cap 180mm	10	ea
181	End Cap	Borfit	End Cap 20mm	2	ea
182	End Cap	Borfit	End Cap 32mm	1	ea
183	End Cap	Borfit	End Cap 63mm	1	ea
184	End Cap	Borfit	End Cap 90mm	2	ea
185	End Cap	Fussion	End Cap Coupler 90mm	4	ea
186	Flow Conditioner		Flow Conditioner 8" Sch 40, Contour	2	ea
187	Floboss		FloBoss S600+, No Model: S600P1/0/B/0/0/0/0, S600P1 - S600+ Base Unit, SN: 214001134, 214001135	2	ea
188	Gas Chromatograph	Rosemount	Gas Chromatograph P/N : 370XA-CSA-6004-3-HE-W-Y	1	ea

189	Gas Meter Diaphragm	Zenner	Gas Meter Diaphragm G.16MA, Center Distance: 130mm, Pmax: 0.5bar, Connector: M30*2, Cyclic Volume: 0.8L, Transmission Method: Magnetic	200	ea
190	Genie A+ Sample Probe		<i>Genie A+ Sample Probe</i>	1	ea
191	Growatt Solar Inverter		<i>Growatt Solar Inverter</i>	3	ea
192	MGRT	Dehan	<i>MGRT merk Dehan</i>	147	ea
193	MGRT	Ergas	<i>MGRT merk ERGAS</i>	18	ea
194	Multifunction Process Calibrator		Multifunction Process Calibrator ADT226, Temperature and Pressure	1	ea
195	Multifunction Process Calibrator		Multifunction Process Calibrator ADT226EX, Temperature And Pressure, Atex Certified Intrinsically	1	ea
196	Pipe		<i>Pipe SMLS-PE 6m (4" S40)</i>	8	btg
197	QOC		<i>QOC 6" #150 three clamp type (Quick Opening Closure) SN: MB2023-071, MB2023-074</i>	2	nos
198	Reducer Kit	Borfit	<i>Reducer Kit 125-90</i>	1	ea

199	Reducer Kit	Borfit	<i>Reducer Kit 25-20</i>	33	ea
200	Reducer Kit	Borfit	<i>Reducer Kit 35-20</i>	1	ea
201	Reducer Tee 180-125	Borfit	<i>Reducer Tee 180-125</i>	2	ea
202	Reducer Tee	Borfit	<i>Reducer Tee 32-20</i>	1	ea
203	Reducer Tee	Borfit	<i>Reducer Tee 63-20</i>	4	ea
204	Reducer Tee	Borfit	<i>Reducer Tee 63-32</i>	2	ea
205	RTD Sensor & Thermowell	WIKA	<i>TW10-F-A-M-DHBUD-N-0024500057G3G3DA025001901J-3Z</i> <i>Z00295ZZZZYQ1Z</i> <i>CERT31-EG3A-BB- TW</i> <i>TR10-B-ZZZZ-14HM-1F5B-ZZ-1F1S-150-0295-60L-Z-ZZ</i> <i>048821-ZA-Z-WIKAOZS</i> <i>TR10-B RTD assembly for additional thermowell</i> <i>Specifications according to data sheet: TE 60.02</i> <i>1xPt100, 4-wire</i> <i>Class A, IEC 60751</i> <i>Temperature range of selected class: -30...+300°C</i> <i>Head/housing: 1/4000, Aluminum, screw cover</i> <i>Cable entry: Thread (female)</i>	2	ea

			Thread size cable entry: 1/2 NPT Transmitter: Without (terminal block) Connection to neck tube: 1/2 NPT Neck tube: Nipple-Union-Nipple Thread size: 1/2 NPT Neck tube material: Stainless steel 316 Neck length [MH/N]: 150 mm (approx. 6 inch) Insertion length [A] [11/A/U2]: 295 mm Diameter measuring insert: 6 mm Sheath material measuring insert: Stainless steel 316L Sealing: Without Measuring insert length (spare) [15]: 488 mm Flanged Thermowell TW10, solid machined Specifications according to data sheet: TW 95.10 Welding options: Full penetration welded Thermowell style: Tapered Unit of measure: Metric (mm) Flange size: ASME 2 inch Pressure rating: Class 600 Flange face: RF (Raised face) Connection to thermometer [N]: 1/2 NPT female Pipe sched. /Intern. nozzle dia.: WIKA (Standard Germany) Insertion length [U]: 245 mm Head length [H]: 57 mm Flange material: Stainless steel 316/316L Material: Stainless steel 316/316L Bar diameter [Bd or F2]: 30 mm. Bore size [B or d1]: 0.260 inch (6.6 mm) Root diameter [Q]: 25 mm Tip diameter [V or F3]: 19 mm		
--	--	--	---	--	--

206	Thermowell Tapperad Drilled Bar Stock	Thermowell Tapperad Drilled Bar Stock TW-T12 1/2 NPT Female x 3/4" NPT Male, SS316 60mm SN: TW-T12-368 s/d TW-T12-375	2	ea
-----	---------------------------------------	---	---	----